

White Paper

# Wi-Fi 6E





With the numbers of end devices growing steadily and the increasing density of IoT devices, the load on the available Wi-Fi frequencies has made communication hardly possible without collisions. For this reason and for 15 years of no changes within the spectrum usages, the Wi-Fi industry actively requested the National Regulatory Agencies for new frequencies. The American regulatory authority FCC has already allocated the full spectrum of 1,200 MHz for Wi-Fi in the 6-GHz band. Since the summer of 2021, at least the first half of the spectrum (500 MHz) has been allocated in Europe, the so-called lower band of 6 GHz. The Wi-Fi Alliance generally extends Wi-Fi 6 by the 6-GHz band, calling it "Wi-Fi 6E". A new era for wireless LAN has begun!

## Focusing on high density

The advantages of Wi-Fi 6 are most apparent in what are known as high-density environments, where very large numbers of Wi-Fi end devices or IoT devices all operate at the same time. Examples are football stadiums, concert venues, convention centers, trade fairs, airports or universities, schools or hospitals and the like. Wi-Fi 6 thus sets new benchmarks and leads to a significant increase in performance. However, this is quickly offset by the exponential growth in the amount of data transmitted per client.

Wi-Fi 6E remedies this by opening up additional spectrum for WLAN access points and clients. This is because the currently available spectrum often represents a bottleneck. For example, the 2.4 GHz frequency band is generally crowded with a high number of clients. And the number of users in the 5 GHz band is also rising steadily, with DFS (radar detection) also posing a problem there.

In Europe, two frequency bands were previously available for Wi-Fi: the 2.4-GHz band (2400–2483.5 MHz, channels 1–13) and the 5-GHz band (5150–5350 MHz, channels 36–64 and 5470–5725 MHz, channels 100–140 as well as 5735-5875 MHz, channels 149-173, yet the latter with a lower transmission power). Operating on the 5-GHz band requires the use of Dynamic Frequency Selection (DFS) on channels 52 to 140. This restricts access points to those channels that are currently free, since channels may be occupied by various systems such as weather radar.

In Europe, for example, the 2.4-GHz band provides a maximum of just three non-overlapping channels with a bandwidth of 22 MHz or four overlap-free channels with a bandwidth of 20 MHz each, whereas the 5-GHz band supports up to 27 of these channels, although not all of them can be used all the time due to the restrictions mentioned above. The recent Wi-Fi standards Wi-Fi 4 (IEEE 802.11n), Wi-Fi 5 (IEEE 802.11ac), and Wi-Fi 6 (IEEE 802.11ax) bundle these channels in order to increase data transfer rates. Permitted, and even required by some standards, are channel widths of 40, 80, and optionally 160 MHz. This decreases the number of usable channels accordingly.



It became clear, for example, that the existing Wi-Fi standards completely filled the existing Wi-Fi spectrum and that a lack of capacity was to be expected as the number of devices continues to grow and the data requirements of applications increase.



Figure 1: Frequency scheme 2.4 GHz, 5 GHz, and 6 GHz

## A major step for Wi-Fi

The American regulatory authority FCC is planning to expand the Wi-Fi spectrum by a further 1200 MHz in the 6-GHz band (5925-7125 MHz), which effectively multiplies the spectrum available for Wi-Fi. This allows an additional 59 channels to be used at 20-MHz bandwidth. Similarly, the number of the frequently used 40- and 80-MHz bandwidth channels increases by 29 and 14, respectively. Even at the extreme of 160-MHz bandwidth channels, the available spectrum allows the use of seven additional channels. On top of that, the available spectrum is a preparation for the upcoming wireless LAN standard Wi-Fi 7, which will be able to create 320 MHz channel widths.

In Europe, the 6 GHz band around 500 MHz (5925-6425 MHz), which can be used exclusively for license-exempt technologies such as Wi-Fi, has also already been approved (for the Low Power Indoor and Very Low Power Portable operating modes, see the following page). So far there has been no agreement on more continuous exclusive spectrum. Nevertheless, the Wi-Fi industry is striving to be able to use the spectrum above 6.425 GHz for wireless LAN one day. Nonetheless, for Europe this additional 500 MHz is the first expansion of the Wi-Fi frequency range in over 15 years. It more than doubles the spectrum available to Wi-Fi. The number of 20-MHz bandwidth channels exclusively for Wi-Fi increases by 24; accordingly, bundling these channels results in 12 additional 40-MHz channels, six 80-MHz channels and, potentially, three extremely wide 160-MHz channels.



## Device classes for the 6 GHz band

### Low Power Indoor

Currently, the global Wi-Fi industry anticipates several different classes of devices for the 6 GHz band. The best-known class is "Low Power Indoor" (LPI). These are devices that may be operated indoors and can use a maximum of 200 mW (23 dBm) EIRP transmission power. In addition, an access point must be operated via a power plug or PoE in Europe, and the use of batteries is prohibited. This is to prevent indoor access points from being operated outdoors in large numbers. There is no such restriction on the client side. It is assumed that the requirement that access points are only to be operated indoors will lead to low outdoor use of clients in 6 GHz. After all, a smartphone is perfectly capable of getting outside and still maintaining a connection to an indoor access point, e.g. in the garden or on the balcony.

#### **Very Low Power**

The other class is called "Very Low Power" (VLP) and describes devices that are usually worn close to the body and span a so-called "Personal Area Network" (PAN). A well-known example of this is AR/VR headsets, which could be wirelessly paired with a smartphone or tablet. Since these devices are portable and can be used outdoors, there is a restriction on transmit power here to only 25 mW (14 dBm). Another use case would be head-up displays in car windows, which also receive their data from an on-board computer or smartphone via Wi-Fi 6E from an on-board computer or smartphone.

### Summary

Opening up the 6 GHz band for Wi-Fi was a further step toward strengthening and expanding the future viability of Wi-Fi technology. More stable Wi-Fi connections through the exclusive use of Wi-Fi 6, combined with significantly more bandwidth and very low latency allow exponential growth of users in Wi-Fi 6E networks.

Wi-Fi 6E transfers existing Wi-Fi 6 features to the 6 GHz band, including orthogonal frequency division multiple access (OFDMA), target wake time (TWT), and multi-user multiple input, multiple output (MU-MIMO). It also enforces the use of the latest security standards, WPA3, for home and corporate networks, and Enhanced Open for open networks such as Wi-Fi hotspots. With the use of the current latest and best Wi-Fi encryption standards, the networks and users should be even better protected.

The advantages of Wi-Fi 6E are most apparent in high-density environments, with very large numbers of Wi-Fi end devices or IoT devices all operating at the same time. Furthermore, Wi-Fi 6E achieves performance levels so far available only to local industrial networks based on the latest cellular standard 5G—however, the investment costs



are just a fraction. This way, state-of-the-art IoT or VR applications will become costeffective.

LANCOM Systems GmbH Adenauerstr. 20/B2 52146 Wuerselen | Germany info@lancom.de www.lancom-systems.com LANCOM, LANCOM Systems, LCOS, LANcommunity and Hyper Integration are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. This document contains statements relating to future products and their attributes. LANCOM Systems reserves the right to change these without notice. No liability for technical errors and / or omissions. 08/2022